

*arr Mega Stack

version: "3.7"

services:

radarr:

container_name: radarr

hostname: Radarr

image: ghcr.io/hotio/radarr

ports:

- "7878:7878"

environment:

- PUID=998

- PGID=100

- UMASK=002

- TZ=Europe/Paris

volumes:

- /srv/path/Files/Radarr/config:/config

- /mnt/OrbiterVideo/movies:/movies

- /mnt/OrbiterVideo/EnfantsFilms:/moviesKids

- /srv/path/Files/QBittorrentVPN/downloads:/downloads

restart: unless-stopped

networks:

- arr

sonarr:

container_name: sonarr

hostname: Sonarr

image: ghcr.io/hotio/sonarr

ports:

- "8989:8989"

environment:

- PUID=998

- PGID=100

- UMASK=002

- TZ=Europe/Paris

volumes:

- /srv/path/Files/Sonarr/config:/config
- /mnt/OrbiterVideo/tvshows:/tvshows
- /mnt/OrbiterVideo/EnfantsSeries:/tvshowsKids
- /srv/path/Files/QBittorrentVPN/downloads:/downloads

restart: unless-stopped

networks:

- arr

qbittorrent:

container_name: qbittorrentvpn

image: ghcr.io/hotio/qbittorrent

ports:

- 8992:8992
- 8118:8118

environment:

- WEBUI_PORTS=8992/tcp,8992/udp
- PUID=998
- PGID=100
- UMASK=0022
- TZ=Europe/Paris
- VPN_ENABLED=true
- VPN_LAN_NETWORK=192.168.1.0/24
- VPN_CONF=wg0
- VPN_IP_CHECK_DELAY=5
- PRIVOX_ENABLED=false
- DEBUG=yes

volumes:

- /srv/path/Files/QBittorrentVPN:/config
- /srv/path/Files/QBittorrentVPN/downloads:/downloads
- /srv/path/Files/QBittorrentVPN/skins:/skins

cap_add:

- NET_ADMIN

sysctls:

- net.ipv4.conf.all.src_valid_mark=1
- net.ipv6.conf.all.disable_ipv6=1

restart: unless-stopped

networks:

- arr

bazarr:

container_name: bazarr
hostname: Bazarr
image: ghcr.io/hotio/bazarr

ports:

- "6767:6767"

environment:

- PUID=998
- PGID=100
- UMASK=002
- TZ=Europe/Paris

volumes:

- /srv/path/Files/Bazarr/config:/config
- /mnt/OrbiterVideo/tvshows:/tvshows
- /mnt/OrbiterVideo/movies:/movies
- /mnt/OrbiterVideo/EnfantsSeries:/tvshowsKids
- /mnt/OrbiterVideo/EnfantsFilms:/moviesKids

restart: unless-stopped

networks:

- arr

jackett:

image: lscr.io/linuxserver/jackett

container_name: jackett

environment:

- PUID=998
- PGID=100
- TZ=Europe/Paris
- AUTO_UPDATE=true

volumes:

- /srv/path/Files/Jackett/config:/config
- /srv/path/Files/Jackett/downloads:/downloads

ports:

- 9117:9117

restart: unless-stopped

networks:

- arr

prowlarr:

image: lscr.io/linuxserver/prowlarr:develop

container_name: prowlarr

environment:

- PUID=998
- PGID=100
- TZ=Europe/Paris

volumes:

- /srv/path/Files/Prowlarr/config:/config

ports:

- 9696:9696

restart: unless-stopped

networks:

- arr

jellyseerr:

image: fallenbagel/jellyseerr:latest

container_name: jellyseerr

environment:

- LOG_LEVEL=debug
- TZ=Europe/Paris

ports:

- 5055:5055

volumes:

- /srv/path/Files/Jellyseerr/config:/app/config

restart: unless-stopped

networks:

- arr

reiverr:

image: ghcr.io/aleksilassila/reiverr:latest

container_name: reiverr

ports:

- 9494:9494

volumes:

- /srv/path/Files/Reiverr/config:/config

restart: unless-stopped

networks:

- arr

flaresolvrr:

DockerHub mirror flaresolvrr/flaresolvrr:latest

image: ghcr.io/flaresolvrr/flaresolvrr:latest

container_name: flaresolterr

environment:

- LOG_LEVEL=debug
- LOG_HTML=false
- CAPTCHA_SOLVER=none
- LANG=en_US #important for yggtorrent for example. Don't change
- TZ=Europe/Paris
- LANG=en_EN

ports:

- "8191:8191"

restart: unless-stopped

networks:

- arr

unpackerr:

image: golift/unpackerr

container_name: unpackerr

volumes:

- /srvpath/Files/QBittorrentVPN/downloads:/downloads

restart: always

user: "998:100"

environment:

- TZ=Europe/Paris
- UN_DEBUG=true
- UN_LOG_FILE=/downloads/unpackerr.log #do not change. Or check dedicated page for unpackerr in this

wiki

- UN_INTERVAL=10m
- UN_START_DELAY=1m
- UN_RETRY_DELAY=5m
- UN_MAX_RETRIES=3
- UN_PARALLEL=1
- # Sonarr Config
- UN_SONARR_0_URL=http://
- UN_SONARR_0_API_KEY=
- UN_SONARR_0_PROTOCOLS=torrent
- # Radarr Config
- UN_RADARR_0_URL=http://
- UN_RADARR_0_API_KEY=
- UN_RADARR_0_PROTOCOLS=torrent

networks:

- arr

networks:

arr:

driver: bridge

Revision #6

Created 1 December 2023 21:44:25 by Admin

Updated 21 November 2024 00:43:45 by Admin