

Homepage

Link

services:

homepage:

image: ghcr.io/gethomepage/homepage:latest

container_name: homepage

ports:

- 5005:3000

volumes:

- /srv/path/to/config:/app/config

- /srv/path1:/data # for widget resources

- /srv/path2:/backup # for widget resources

- /var/run/docker.sock:/var/run/docker.sock # (optional) For docker integrations

environment:

- LOG_LEVEL=debug

- HOMEPAGE_ALLOWED_HOSTS=*

restart: unless-stopped

HOMEPAGE_ALLOWED_HOSTS

As of v1.0 there is one required environment variable to access homepage via a URL other than `localhost`, `HOMEPAGE_ALLOWED_HOSTS`. The setting helps prevent certain kinds of attacks when retrieving data from the homepage API proxy.

The value is a comma-separated (no spaces) list of allowed hosts (sometimes with the port) that can host your homepage install. See the [docker](#), [kubernetes](#) and [source](#) installation pages for more information about where / how to set the variable.

`localhost:3000` and `127.0.0.1:3000` are always included, but you can add a domain or IP address to this list to allow that host such as `HOMEPAGE_ALLOWED_HOSTS=gethomepage.dev,192.168.1.2:1234`, etc.

If you are seeing errors about host validation, check the homepage logs and ensure that the host exactly as output in the logs is in the `HOMEPAGE_ALLOWED_HOSTS` list.

This can be disabled by setting `HOMEPAGE_ALLOWED_HOSTS` to `*` but this is not recommended.

