

# qBittorrent

[Link](#)

```
---
version: "2.1"
services:
  qbittorrent:
    image: lscr.io/linuxserver/qbittorrent
    container_name: qbittorrent
    environment:
      - PUID=1000
      - PGID=1000
      - TZ=Europe/London
      - WEBUI_PORT=8080 # 8996
    volumes:
      - /path/to/appdata/config:/config
      - /path/to/downloads:/downloads
    ports:
      - 6881:6881
      - 6881:6881/udp
      - 8080:8080 # 8996:8996
    restart: unless-stopped
```

The webui is at `<your-ip>:8080` and the default username/password is `admin/adminadmin`.

Change username/password via the webui in the webui section of settings.

## WEBUI\_PORT variable

Due to issues with CSRF and port mapping, should you require to alter the port for the webui you need to change both sides of the `-p 8080` switch AND set the `WEBUI_PORT` variable to the new port.

For example, to set the port to 8090 you need to set `-p 8090:8090` and `-e WEBUI_PORT=8090`

This should alleviate the "white screen" issue.

If you have no webui, check the file `/config/qBittorrent/qBittorrent.conf`

edit or add the following lines

```
WebUI\Address=*
```

```
WebUI\ServerDomains=*
```

---

Revision #4

Created 12 December 2021 10:44:06 by Admin

Updated 21 November 2024 22:16:21 by Admin